

## RG ZIRCONIUM flap wheels on 6mm-shaft

### Description:

Zirconium flaps and X-weight backing. 6-mm diameter cylindrical shaft.

### Main features and benefits:


Highly efficient removal. Since flaps are quite rigid, do not use this product where high stresses could result in cloth breakage.

### Recommended applications:

Cleaning welded surfaces or steel, stainless steel and titanium parts.

### Work surfaces:

Stainless steel, standard steel, titanium.

diam/th/shaft	max	rpm		P40	P60	P80	P120
30x15x6	31.800	22.900	10	RG0505 •	RG0506 •	RG0507 •	RG0508
30x20x6	31.800	22.900	10	RG0509 •	RG0510 •	RG0511 •	RG0512
40x15x6	23.800	17.100	10	RG0513	RG0514	RG0515	RG0516
40x20x6	23.800	17.100	10	RG0517 •	RG0518 •	RG0519 •	RG0520 •
50x15x6	19.000	13.700	10	RG0521	RG0522	RG0523	RG0524
50x20x6	19.000	13.700	10	RG0525	RG0526	RG0527	RG0528
50x25x6	19.000	13.700	10	RG0529	RG0530	RG0531	RG0532
50x30x6	19.000	13.700	10	RG0533 •	RG0534 •	RG0535	RG0536
60x30x6	16.100	11.500	10	RG0537 •	RG0538 •	RG0539 •	RG0540 •
60x40x6	16.100	11.500	10	RG0541	RG0542	RG0543	RG0544
80x30x6	11.800	8.600	10	RG0545	RG0546	RG0547	RG0548